

# NYU Center for Data Science: DS-GA 1003

## Machine Learning and Computational Statistics (Spring 2018)

Brett Bernstein

April 20, 2018

**Instructions:** Following most lab and lecture sections, we will be providing concept checks for review. Each concept check will:

- List the lab/lecture learning objectives. You will be responsible for mastering these objectives, and demonstrating mastery through homework assignments, exams (midterm and final), and on the final course project.
- Include concept check questions. These questions are intended to reinforce the lab/lectures, and help you master the learning objectives.

You are strongly encourage to complete all concept check questions, and to discuss these (and related) problems on Piazza and at office hours. However, problems marked with a (★) are considered optional.

## Boosting: Concept Check

### Boosting Learning Objectives

- Compare learning a linear model on a fixed set of basis functions on the input space, and an "adaptive basis function model" where the basis functions are learned.
- In particular, explain the "recipe" for an adaptive basis function model in terms of the base hypothesis space, and combined hypothesis space.
- Give psuedo-code for forward stagewise additive modeling (FSAM).
- Give the ingredients for gradient boosting machines; in particular, be able to explain why we need a [sub]differentiable loss function w.r.t. the prediction.
- Explain how gradient boosting uses "functional" gradient descent - i.e. learning the basis function (i.e. function in the base hypothesis space) that is closest to the negative gradient step direction given the current prediction function.

- Explain options for step sizes (line search and shrinkage parameter/learning rate).
  - Explain variations on gradient boosting (stochastic gradient boosting, and column subsampling).
1. (★) Show the exponential margin loss is a convex upper bound for the 0 – 1 loss.
  2. Show how to perform gradient boosting with the hinge loss.
  3. Suppose we are using gradient boosting. On each step we can do a better job of fitting the pseudoresiduals if we allow for deeper trees. Why might deep trees be discouraged while gradient boosting?